


FFB400: Bidirectional Remote Control for EM100, Minifant M99 , EMX90, EMX250 and Many Third-party Machines



- Bidirectional radio technology
- Various frequency channels with automatic selection of the best operating frequency
- Range monitoring with safety shut down when range is exceeded.
- Reduced battery use when a shorter range is required.
- Compatible to machines of Krendl, SHS, Isoblow, Thermoblow and many more



Transmitter and receiver unit of the FFB400 interchange digital signals with bidirectional radio technology. That means signal validations are interchanged and so assures interference-free operation. The receiver only acts upon orders which have been validated. The remote will not send new instructions until validation is received.

Remote

4 buttons on IP65 plastic case, colour: black, with battery compartment for 2 x AAA and 2 red and green LEDs with the following functions:

- ▶ Air ON
- ▶ Material ON
- ▶ Air and material ON
- ▶ Material OFF, air ON
- ▶ Additional/ reserve channel
- ▶ Battery and radio-communication function display with 2 LEDs
- ▶ Keypad lock (to prevent unintentional switching on of machine)

Receiver

The sturdy plastic casing, magnetic foot and integrated aerial make it ideal for blowing machines with a control circuit.



Magnetic foot

Optional Accessories



Sport-case for hand-held controls (product no. 5016)



Case with belt loop for remote (product no. 4716)



Technical Data	
Operating frequency	434 MHz
Short circuit, surge- and under voltage protected radio technology	✓
Remote	
Battery life time	approx. 200 working hours
Switch on delay between air and material	0...3 seconds (adjustable)
Dimensions (W×H×D)	22×65×120 mm
Receiver	
Cable length	approx. 4 m
Dimensions (W×H×D)	45×82×113 mm